
TRIANGO 100

OPTIMAL LIGHT FOR PROCEDURES AND EXAMINATIONS



A PROCEDURE LIGHT THAT MEETS YOUR REQUIREMENTS.



CUSTOMIZED VERSIONS

The modular design of TRIANGO 100 allows the user to select a version with features that meet the needs of their specific application. Applications include:

- Clinics & hospitals
- Doctor's offices & medical centers
- Veterinary clinics
- Operative dermatology
- Endoscopy
- Emergency rooms
- Intensive care units
- Minimally invasive & outpatient surgery
- Maxillofacial surgery
- Laboratories

UNIQUE UNOBTUSIVE DESIGN

The contoured light head allows a practitioner to position the light as close as possible to the patient.

SHADOWS ELIMINATED

Handling lighting during an examination often results in shadowing. That is not the case thanks to the uniform illumination of TRIANGO 100.

MINIMAL MAINTENANCE REQUIRED

The sealed housing keeps particles and liquids from permeating the light, making it ideal for facilities.



TECHNICAL DATA
ONLINE

waldmannlighting.com

PRODUCT
VIDEOS




suitable for
Laboratories,
medical practices,
clinics, etc.

**APPROVED
MEDICAL DEVICE**


compliant with
EN 60601-1
EN 60601-2-41

Diamond cluster optics


For uniform light
with 100,000 lux @ 1 meter

**Unique arm system**


Large range of motion
and long reach

**Intuitive operation**

Simple operation with
an easy-to-reach keypad

**Ideal color temperature**

Optionally adjustable to three levels
(3700 K / 4300 K / 4700 K)*


**Focusable ***

Adjustable light field of 7 inches
to 11 inches

**Endo mode ***

Optimal light conditions
for endoscopic and minimally
invasive procedures

* optional



Model	Dimmable	Color changing	Focusable	Endo mode	Part #
Triango 100-1 C	*				D16072000
Triango 100-3 C	*	*			D16073000
Triango Focus 100-1 C	*		*		D16074000
Triango Focus 100-3 C	*	*	*		D16075000
Triango Endo 100-1 C	*			*	D16076000
Triango 100-1 W	*				D16077000
Triango 100-3 W	*	*			D16078000
Triango Focus 100-1 W	*		*		D16079000
Triango Focus 100-3 W	*	*	*		D16080000
Triango Endo 100-1 W	*			*	D16081000
Triango 100-1 F	*				D15915000
Triango 100-3 F	*	*			D15916000
Triango Focus 100-1 F	*		*		D15917000
Triango Focus 100-3 F	*	*	*		D15918000
Triango Endo 100-1 F	*			*	D15976000



Ceiling version



Wall version



Floor stand version

TRIANGO 100 technical data

Illumination power**	100 000 Lux @ 1 m (39.4 in)
Light field Ø **	Fixed: 7 inches / Focusable: 7-11 inches*
Dimming **	4 dimming levels on all models
Color temperature **	Fixed: 4300 K (100-1 models) Adjustable: 3700 K / 4300 K / 4700 K* (100-3 models)
Color rendering index **	Ra = 95
System of protection	IP43 (luminaire head)
Ergonomic handle	Sterilizable handle, optional disposable cover

** -10% / +20% tolerance

*optional

Headquarters in Germany

Center of Expertise for Healthcare:

USA

Waldmann Lighting Company
9 W. Century Drive
Wheeling, IL 60090 USA
Telephone +1 847 520 1060
Fax +1 847 520 1730
www.waldmannlighting.com
waldmann@waldmannlighting.com

HERBERT WALDMANN GMBH & CO. KG

Peter-Henlein-Straße 5
78056 Villingen-Schwenningen Germany
Tel.: +49 7720 601-0
Tel. +49 7720 601-100 (sales)
Fax +49 7720 601-290
www.waldmann.com
sales.germany@waldmann.com

DERUNGS LICHT AG

Hofmattstrasse 12
9200 Gossau
Switzerland
Phone +41 71 388 11 66
Fax +41 71 388 11 77
www.derungslicht.com
mailbox@derungslicht.com

Derungs Licht AG is a member
of the Waldmann Group.

Derungs 
MEDICAL LIGHTING

