

# Surface-mounted luminaire ACURIA.perfect APA 1450/850/MS

114311000-00806645

# Waldmann **W**

ENGINEER OF LIGHT.



<b>light source</b>	LED
<b>work equipment</b>	without
<b>connected load</b>	24 V, DC
<b>power consumption</b>	env. 12 W
<b>luminous flux</b>	approx. 1400 lm
<b>luminous efficiency</b>	approx. 117 lm/W
<b>light distribution</b>	direct
<b>beam angle</b>	91°
<b>color temperature</b>	neutral white
<b>color temperature</b>	approx. 5,000 K
<b>color rendering index (CRI)</b>	>= 80
<b>chromaticity tolerance LED</b>	< 3 SDCM
<b>glare control</b>	screen
<b>luminance (L65)</b>	<= 5200 cd/m <sup>2</sup>
<b>unified glare rating (4H 8H)</b>	<= 22
<b>technology</b>	multi-stage switchable
<b>operation</b>	external
<b>housing</b>	aluminum; anodized; aluminum colored anodized
<b>cover</b>	glass screen
<b>weight (net)</b>	env. 1.06 kg (2.34 lbs)
<b>mains lead</b>	built-in plug; M12-A-5
<b>fastening</b>	snap-fit
<b>dimension</b>	A=390 mm (15.35")
<b>special features</b>	ADVANCED package



## light distribution

