



Dmed® **triango** 30 W Spec Sheet
 D15-175-101 DERUNGS

PROJECT:		TYPE:		QUANTITY	
-----------------	--	--------------	--	-----------------	--

Electrical:	
Nominal input voltage	100-240V
Frequency range	50 / 60Hz
Power consumption	30W (42-52VA)
Input current	0.42A
Integrated electronic transformer	24V DC output
Approval - Safety	ETL/cETL
User interface	Continuously dimmable rotary switch on the head



Illumination:	
Fitted with	LED Technology
Central illuminance at 1.0m	60,000 lux
Light field diameter d10 at 1.0m	Ø = 16 cm (6.3in)
Light field diameter d50 at 1.0m	Ø = 8.5 cm (3.3in)
Depth of illumination L1 + L2	120cm (47.24in)
Color Temperature	4500 K
Color Rendering Index Ra	>95
Life time	40000h



Weight:	
Light head	3 kg (6.6lbs)
triango 30 C (includes light head)	15 kg (33lbs)
Luminaire Materials	Head – polycarbonate & acrylonitrile butadiene styrene copolymer (PC &ABS); Arm – metal
Fastening	Mount to structural wall

Classification:	
triango 30	Class I; FDA Class I
Degree of protection as per IEC 529	IP 20
Light head	IP 43 (horizontal position)
Electrical safety test according to:	AAMI ES60601-1, CSA C22.2#60601-1, IEC/EN 60601-1, IEC/EN 60601-2-41, IEC/EN 60601-1-2
Special feature	Removable Sterilizable Handle included

Component List - Included

#	Part Number	Description
1	D74-285-000	Dome Cover
2	D74-544-100	Spring Balanced Arm
3	D15-312-000	Head, Triango 30, 24V, LED
4	US4-002-414	Dome Cover Kit w/ Collar

Additional Information Available (Manuals)

1	Call Factory	Triango Pre-Install Guide
2	Included	Triango Manual
3	Call Factory	Triango Spare Parts Manual

