

# Recessed luminaire ACURIA.perfect APE 8000/850/MS

114325000-00806659

# Waldmann **W**

ENGINEER OF LIGHT.



**light source**  
**work equipment**  
**connected load**  
**power consumption**  
**luminous flux**  
**luminous efficiency**  
**light distribution**  
**beam angle**  
**color temperature**  
**color temperature**  
**color rendering index (CRI)**  
**chromaticity tolerance LED**  
**glare control**  
**luminance (L65)**  
**unified glare rating (4H 8H)**  
**technology**  
**operation**  
**housing**  
  
**cover**  
**weight (net)**  
**mains lead**  
**fastening**  
**dimension**  
**special features**

LED  
 without  
 24 V, DC  
 env. 56 W  
 approx. 7,600 lm  
 approx. 136 lm/W  
 direct  
 92°  
 neutral white  
 approx. 5,000 K  
 >= 80  
 < 3 SDCM  
 screen  
 <= 4200 cd/m<sup>2</sup>  
 <= 22  
 multi-stage switchable  
 external  
 aluminum; anodized; aluminum  
 colored anodized  
 glass screen  
 env. 4.64 kg (10.23 lbs)  
 built-in plug; M12-A-5  
 snap-fit  
 A=748 mm (29.45")  
 ADVANCED package

## light distribution

