



light source  
 work equipment  
 connected load  
 Power consumption  
 luminous efficacy  
 colour temperature  
 color rendering index (CRI)  
 chromaticity tolerance LED  
 System of protection  
 class of protection  
 technology  
 operation  
 luminaire body  
 lamp cover  
 tubular sections

balance of articulation joints  
 weight (net)  
 mains lead

Fastening  
 lens; dimensions  
 lens material  
 lens; diopters  
 special features

LED  
 Energy efficiency category A/A+/A++  
 electronic plug-in ballast  
 100-240 V; 50/60 Hz  
 approx. 13 W  
 approx. 57 lm/W  
 neutral white, approx. 5000 K  
 >= 90 (R9>50)  
 3 SDCM  
 IP20  
 II  
 multi-stage switchable, continuously dimmable  
 multi-function switch  
 plastic, untreated, black  
 screen, milky, Polyamide  
 tubular aluminium section, anodized, aluminium coloured  
 anodised  
 spring  
 approx. 2.5 kg (5.51 lb)  
 approx. 3.6 m (11.81 in); mains plug  
 BS 1363  
 CEE 7/XVI  
 NEMA 1-15P  
 screw-down flange  
 Ø 160 mm (6.29 in)  
 glass  
 3,5  
 light characteristic can be adjusted with a three-way switch,  
 arm length 31"



BS 1363



CEE 7/XVI



NEMA 1-15P

**illuminance**

distance: 15 cm

Em: 4099 lx  
 Emax: 5537 lx  
 Emin: 1894 lx

