



<b>light source</b>	LED
<b>work equipment</b>	without
<b>connected load</b>	22-26 V, DC
<b>power consumption</b>	env. 13 W
<b>luminous flux</b>	approx. 1.650 lm
<b>luminous efficiency</b>	approx. 127 lm/W
<b>light distribution</b>	direct
<b>beam angle</b>	85° / 101°
<b>color temperature</b>	neutral white approx. 5.000 K
<b>color rendering index (CRI)</b>	>= 80
<b>chromaticity tolerance LED</b>	< 4 SDCM
<b>glare control</b>	screen
<b>system of protection</b>	IP 54
<b>class of protection</b>	III
<b>technology</b>	multi-stage switchable
<b>operation</b>	external
<b>housing</b>	aluminium/plastic; anodised, painted; aluminium colored anodised Acrylic satine
<b>cover</b>	
<b>weight (net)</b>	env. 0,393 kg (0.866 lb)
<b>mains lead</b>	built-in plug; M12-A-5
<b>design</b>	mounted version
<b>fastening</b>	bracket
<b>dimensions</b>	A = 475mm, Cmin = 415mm, Cmax = 460mm A = 18.7in, Cmin = 16.3in, Cmax = 18.1in 475mm; 35mm; 38.5mm (18.7in;1.38in;1.51in)
<b>special features</b>	through-wired; ADVANCED package

