



M12-A-5



<b>light source</b>	LED
<b>work equipment</b>	without
<b>connected load</b>	22-26 V, DC
<b>power consumption</b>	env. 17 W
<b>luminous flux</b>	approx. 2.200 lm
<b>luminous efficiency</b>	approx. 129 lm/W
<b>light distribution</b>	direct
<b>beam angle</b>	85° / 101°
<b>color temperature</b>	neutral white approx. 5.000 K
<b>color rendering index (CRI)</b>	>= 80
<b>chromaticity tolerance LED</b>	< 4 SDCM
<b>glare control</b>	screen
<b>system of protection</b>	IP 54
<b>class of protection</b>	III
<b>technology</b>	multi-stage switchable
<b>operation</b>	external
<b>housing</b>	aluminium/plastic; anodised, painted; aluminium colored anodised
<b>cover</b>	Acrylic satine
<b>weight (net)</b>	env. 0,490 kg (1.08 lb)
<b>mains lead</b>	built-in plug; M12-A-5
<b>design</b>	mounted version
<b>fastening</b>	bracket
<b>dimensions</b>	A = 615mm, Cmin = 555mm, Cmax = 600mm A = 24.2in, Cmin = 21.8in, Cmax = 23.62in 615mm; 35,mm; 38.5mm (24.2in; 1.38in;1.51in)
<b>special features</b>	ADVANCED package

