

**Examination Luminaire**  
**HALUX N30-1 P SH**  
 # D15991110



|                                       |   |
|---------------------------------------|---|
| <b>fitted with</b>                    | LED module - energy efficiency category A+  |
| <b>illumination field @ 50cm</b>      | Ø 18cm  |
| <b>illumination @ 50cm</b>            | 30,000lx  |
| <b>color rendering index (CRI)</b>    | > 93  |
| <b>color temperature</b>              | 4400K   |
| <b>work equipment</b>                 | electronic plug-in transformer  |
| <b>mains lead</b>                     | approx. 5.6ft (1.7m)  |
| <b>luminaire body</b>                 | polycarbonate & acrylonitrile butadiene styrene copolymer (PC & ABS)  |
| <b>weight (net)</b>                   | approx. 2.9lbs (1.3kg)  |
| <b>power consumption</b>              | 8W  |
| <b>usage</b>                          | keypad at luminaire head  |
| <b>balance of articulation joints</b> | friction  |
| <b>class of protection</b>            | II  |
| <b>accessory</b>                      | roll support, rail fastening with removal protection, table clamp with removal protection, universal fastening with removal protection, extension arm with removal protection, wall bracket with removal protection |
| <b>norms</b>                          | EN 60601-1; EN 60601-2-41   |
| <b>special features</b>               | continuously dimmable, maintenance free   |
| <b>fastening</b>                      | fastening pin (Ø 16mm)  |
| <b>mounting included</b>              | floorstand  |
| <b>order number</b>                   | D15991110 - pure white  |

light distribution

