

MEDICAL LED HIGHLIGHTS
SHINE A LIGHT ON YOUR APPLICATION



TRIANGO 100

MINOR PROCEDURE LIGHT

- Light output - 100,000 lx / 1 m
- Light field - 7" / 1 m
Optional: 7 - 11"
- Color temperature: 4300K (100-1 models)
Optional: 3700K, 4300K, 4700K (100-3 models)
- CRI >95
- Dual and single head mounts available
- Mounting options: ceiling, wall or rolling floor stand
- 50,000 hours of LED life (L70)
- Electronics integrated for safety and energy efficiency
- Large turning radius and newly designed TENO arm system for easy positioning
- Totally sealed design for easy sanitizing
- Simple operation with easy to reach keypad
- Diamond optic design reduces shadows
- Complies with EN 60601-1 and EN 60601-2-41
- ETL/cETL



TRIANGO 80

MINOR PROCEDURE LIGHT

- Light output - 80,000 lx / 1 m
- Light field - 7" / 1 m
- Color temperature: 4500K
- CRI >95
- Single head mount available
- Mounting options: ceiling, wall or rolling floor stand
- 50,000 hours of LED life (L70)
- Continuously dimmable
- No heat directed at patient or practitioner
- Sterilizable handle (covers are also available)
- High energy efficiency at 30W
- Complies with EN 60601-1 and EN 60601-2-41
- ETL/cETL



VISIANO 20-2

EXAMINATION LIGHT

- Light output - 60,000 lx / 0.5 m
- Light field - 8.3" / 0.5 m
- Color temperatures: 3500K and 4500K
- CRI >95
- Mounting options: ceiling, clamp, wall, rail or floor stand
- 360° turning radius at the luminaire head
- Four dimming levels
- Ergonomic controls on head allow for one-handed operation
- Totally sealed design for easy sanitizing
- Electronics integrated for maximum safety and energy efficiency
- Strong, aluminum frame and spring-balanced friction joints
- Diamond optic design reduces shadows
- Complies with EN 60601-1 and EN 60601-2-41
- ETL/cETL



VISIANO 10-1 COMPACT EXAMINATION LIGHT

- Light output - 50,000 lx / 0.5 m
- Light field - 7" / 0.5 m
- Color temperature: 4400K
- CRI >93
- Mounting options: ceiling, clamp, wall, rail or floor stand
- 280° turning radius at the luminaire head
- Ergonomic controls on head for one-handed operation
- Electronics integrated for safety and energy efficiency
- Ergonomic handle and high quality gooseneck arm for easy positioning
- Intuitive operation using I/O switch
- Totally sealed design for easy sanitizing
- Diamond optic design reduces shadows
- Complies with EN 60601-1 and EN 60601-2-41
- ETL/cETL



HALUX N50 EXAMINATION LIGHT

- Light output - 50,000 lx / 0.5 m
- Light field - 7" / 0.5 m
- 4400K color temperature or color changing option with 3300K, 3800K and 4400K color temps
- CRI >93
- Mounting options: rail, clamp, wall, rolling stand
- Fast cleaning thanks to closed design
- Maintenance-free
- High-quality materials and durable LED technology
- Safe and easy positioning
- Large homogeneous light field for maximum visual comfort
- 5-stage dimmable
- Complies with EN 60601-1 and EN 60601-2-41
- ETL/cETL



HALUX N30 EXAMINATION LIGHT

- Light output - 30,000 lx / 0.5 m
- Light field - 7" / 0.5 m
- Color temperature: 4400K
- CRI >93
- Mounting options: rail, clamp, wall, rolling stand
- Fast cleaning thanks to closed design
- Maintenance-free
- High-quality materials and durable LED technology
- Safe and easy positioning
- Continuously dimmable
- External mains adapter
- Complies with EN 60601-1 and EN 60601-2-41
- ETL/cETL



OPTICLUX LED MAGNIFIER

- Light output - 6,000 lx / 0.15 m
- Color temperature: 6500K
- Color rendering properties: CRI >93, R9 >90, R13 >95
- Available as a ceiling version and pin version with mounting accessories for walls, tables, rails and rolling floor stands
- Magnification 1.88X (3.5 diopter)
- 6.3" specially-treated hard acrylic magnifier lens with protective lens cover
- Continuously dimmable 100% of 10%
- Optional Wood light: Peak at 365 nm
- ETL/cETL



TEVISIO LED MAGNIFIER

- Color temperature: 5000K
- CRI >90
- 48 premium LEDs surround premium glass magnifier
- 1.88X (3.5 diopter) or 1.88X + 3X (3.5 diopter + 8 diopter) magnification options
- Additional 1.88X (3.5 diopter) lens also available
- 50,000 hours maintenance-free LED life
- Housing made of anodized aluminum
- Spring-balanced arm for easy adjustments
- Luminaire head features integrated touch panel for on/off, dimming or segment switching
- IP20, double-insulated
- 11-foot cord with US plug
- ETL/cETL



COMING SOON!

OPTICLUX Handheld EXAMINATION LIGHT

- Light output - 8,000 lx / 0.15 m
- Color temperature: 6500K
- Color rendering index Ra = 95
- Acrylic glass lens of 3.5 diopters
- Continuously dimmable
- Optional with Wood light: Maximum value at 365 nm
- Flexible charging via USB interface
- > 3 hours battery life
- Maintenance-free
- Ergonomic: Perfect handling for right- and left-handers
- EN 60601-1



Waldmann Lighting Company

9 Century Drive
Wheeling, Illinois 60090
www.waldmannlighting.com

PR348.071922

Telephone (847) 520 1060
Fax (847) 520 1730
waldmann@waldmannlighting.com

Waldmann **W**
ENGINEER OF LIGHT.