

Waldmann **W**

ENGINEER OF LIGHT.

NORTH AMERICA

ARCHITECTURAL TUBULAR LIGHTING





RL70 SERIES

The RL70 Series of linear fluorescent tubular luminaires offers an ideal solution for a variety of lighting applications. From rugged, large scale, outdoor installations, to sophisticated, intricately designed interior décor, the RL70 Series offers flexibility for your difficult

lighting design requirements. These luminaires are compatible with almost all dimming control systems, offering flexible, easily controlled, energy-efficient lighting solutions. The RL70 Series can be configured with a variety of T5 and T8 lamp options, as well as

electronic ballasts mounted inside the luminaire or remotely, making it ideal for any linear lighting application. A variety of mounting options are available for endless design possibilities and ease of installation and maintenance.





RL70 SERIES

RL70 luminaires have an outer diameter of only 2.75" (70mm) and are constructed with impact resistant, waterproof polymer tubes that resist UV radiation for long life.

Features include:

- Dimming with virtually any available dimming system
- Available in lengths from 30 to 84 inches
- IP67 waterproof


- 360° illumination available (X and DX versions)
- 180° illumination for end to end light (H and HD versions)
- Daisy-chaining for linear runs
- Available in T5HO, T5, and T8 lamps
- Other options may be available, consult factory



RL70E-132 H



RL70E-132 X




See spec sheet for dimensions A & B



RL70 SERIES – ORDERING MATRIX

Select from the following criteria for configuring the RL70 for your application.


Note: Some configurations may not be possible due to supplier availability. Factory will advise on any necessary changes. A nine-digit part number will be assigned to each configuration at time of order. Please call factory for other options at (800) 634-0007.



RL70 End Caps















RL70 Electrical Quick Disconnect



Typical Installation w/Canopy Kit Option

MOUNTING OPTIONS FOR RL70 SERIES

		Model	Order Numbers
		Pendant Ring Bracket Ring: Anodized Aluminum Wire: Stainless Steel	190 173 039
		Surface Ring Bracket Ring: Anodized Aluminum Screw: Galvanized Steel	190 175 019
		Pendant Strap Bracket Strap: Stainless Steel Wire: Stainless Steel	190 178 029
		Surface Strap Bracket Strap: Stainless Steel Surface Mount: Stainless Steel	190 147 019
		Vertical Pendant Bracket Bracket: Anodized Aluminum Wire: Stainless Steel	190 204 029
		Decorative Aluminum End Caps Closed End With Opening (for cable)	330 345 010 330 345 020
		Canopy Kit 6" Canopy with feed hole 6" Canopy without feed hole	US0 300 200 US0 300 210



RL70EP-132 X

RL70EP SERIES

The RL70EP Series of linear fluorescent luminaires features soft glow freestanding light columns ideal for mounting in both exterior and interior applications. Their slim tubular design is an innovative way of illuminating public areas, which have unique specification requirements. Train stations, public parks, restaurants, malls, as well as pathways and decorative gardens are just some of the endless applications that lend themselves to the RL70EP Series.



RL70EP SERIES

The RL70EP Series uses our 2.75" (70mm) outer diameter tube, which is waterproof, impact-resistant, and uses a specially designed acrylic polymer. It resists weather and UV radiation for long tube life and color clarity. The pedestals are vandal resistant and are suitable for indoor or outdoor applications. With their slim, minimalistic design, the RL70EP Series works perfectly for both new construction and renovation projects.

Features include:



- Dimming with virtually any available system
- Indoor free-standing base for portable applications
- Bolt-down vandal resistant flange
- Lengths range from 52 to 90 inches with a 2.75" (70mm) outer dimension
- IP67 waterproof
- 360° illumination
- Available in T5HO, T5, and T8 lamp technologies
- Impact resistant polymer tubes
- Other options may be available, consult factory



RL70EP-132 X
Exterior







RL70EP-132 X
Interior



RL70EP PEDESTAL SERIES – ORDERING MATRIX

Select from the following criteria for configuring the RL70 for your application.

Note: Some configurations may not be possible due to supplier availability. Factory will advise on any necessary changes. A nine-digit part number will be assigned to each configuration at time of order. Please call factory for other options at (800) 634-0007.





RL40 SERIES

The RL40 Series is a waterproof, linear fluorescent tubular luminaire that features a slim 1.57" (40mm) outer diameter tube. This specially designed polymer tube is impact-resistant and resists UV radiation for long term tube life and color clarity. The smaller design is architecturally pleasing and ideal for illuminating compact areas where space is limited. A variety of mounting brackets are available for easy installation in both exterior and interior applications.

Features include:


- Internal or remote ballasts
- Available in lengths from 26 to 80 inches
- IP67 waterproof
- 180 degree light distribution
- Available in T5HO, T5, and T8 lamps
- Tinted gel sleeves optional for unique color application
- Other options may be available, consult factory



RL40 SERIES – ORDERING MATRIX

Select from the following criteria for configuring the RL40 for your application.


Note: Some configurations may not be possible due to supplier availability. Factory will advise on any necessary changes. A nine-digit part number will be assigned to each configuration at time of order. Please call factory for other options at (800) 634-0007.




RL40 End Caps



RL40 Electrical Connection

















Typical Installation w/ Canopy Kit Option



See Spec Sheet for Details A & B

MOUNTING OPTIONS FOR RL40 SERIES

		Model	Order Numbers
		Pendant Ring Bracket Ring: Anodized Aluminum Wire: Stainless Steel	190 176 029
		Surface Ring Bracket Ring: Anodized Aluminum Screw: Galvanized Steel	190 177 019
		Pendant Strap Bracket Strap: Stainless Steel Wire: Stainless Steel	190 179 049
		Surface Strap Bracket Strap: Stainless Steel Surface Mount: Stainless Steel	190 174 019
		Surface Spring Clip Spring Band: Galvanized Steel	306 266 022
		Vertical Pendant Bracket Bracket: Anodized Aluminum Wire: Stainless Steel * Available only with 180° light distribution, 360° light distribution only available in RL70 Series.	190 203 M19
		Decorative Aluminum End Caps Closed End With Opening (for cable)	330 345 040 330 345 030
		Canopy 6" Canopy Kit with feed hole 6" Canopy Kit without feed hole	US0 300 200 US0 300 210

USA

Waldmann Lighting Company
9, W. Century Drive
Wheeling, Illinois 60090, USA
Phone +1 847 520-1060
Fax +1 847 520-1730
Toll Free +1 800 634 0007
www.waldmannlighting.com
waldmann@waldmannlighting.com

FRANCE

Waldmann Eclairage S.A.S.
Z.I. Rue de l'Embranchement
F-67116 REICHSTETT
Adresse postale :
BP 23431 Reichstett
F-67455 MUNDOLSHEIM Cedex
Phone +33 (0) 388209588
Fax +33 (0) 388209568
www.waldmann.com
info-fr@waldmann.com

ITALY

Waldmann Illuminotecnica S.r.l.
Via della Pace, 18 A
IT-20098 San Giuliano Milanese (MI)
Phone +39 02 98 24 90 24
Fax +39 02 98 24 63 78
www.waldmann.com
info-it@waldmann.com

NETHERLANDS

Waldmann Lichttechniek BV
Lingewei 19
NL-4004 LK Tiel
Phone +31 (0) 344 - 631019
Fax +31 (0) 344 - 627856
www.waldmann.com
info-nl@waldmann.com

AUSTRIA

Waldmann Lichttechnik Ges.m.b.H.
Gewerbepark Wagram 7
AT-4061 Pasching/Linz
Phone +43 (0)722967400
Fax +43 (0)722967444
www.waldmann.com
info-at@waldmann.com

SWITZERLAND

Waldmann Lichttechnik GmbH
Benkenstasse 57
CH-5024 Küttigen
Phone +41 (0)62 839 1212
Fax +41 (0)62 839 1299
www.waldmann.com
info-ch@waldmann.com

UK

Waldmann Lighting Ltd.
Holme Well Road
Middleton
GB-Leeds LS 10 4TQ
West Yorkshire
Phone +44 1132775662
Fax +44 1132775775
www.waldmann.com
enquiries@waldmannlighting.co.uk

GERMANY

Herbert Waldmann GmbH & Co. KG
Postfach 50 62
D-78057 Villingen-Schwenningen
Phone +49 7720 601-100
Fax +49 7720 601-290
www.waldmann.com
info@waldmann.com

CHINA

Waldmann Lighting (Shanghai) Co. Ltd.
Part A, No. Five Normative Workshop
199 Changjian Road, Baoshan
CN-Shanghai, P.R.C. 200949
Phone +86 21 5169-1799
Fax +86 21 3385-0032
www.waldmann.com
s.lo@waldmann.com.cn

SINGAPORE

Waldmann Lighting Singapore Pte. Ltd.
Blk 168, Jalan Bukit Merah,
#04-09B, Connection One, Tower 3,
Singapore 150168
Phone +65 62758300
Fax +65 62758377
www.waldmann.com
sales@waldmann.com.sg

SWEDEN

Waldmann Ljusteknik AB
Skebokvarnsvägen 370
SE-124 50 Bandhagen
Phone +46 8 990 350
Fax +46 8 991 609
www.waldmann.se
hk@idecenter.se