

# TAMETO

## WORKSTATION LIGHTING

### FEATURES:

- Various lengths for different bench widths and lighting requirements
- Up to 60% energy savings and up to 40% higher illuminance when compared to conventional CFL lamps
- LED or T5 fluorescent lamp options with a service life of up to 50,000 hours (LED) or 24,000 hours (fluorescent)
- Fixed or suspended installation options available
- Minimal heat generation
- Integrated T-slots allow direct installation into truss type workstations
- Closed design for cleanroom applications
- Extremely strong aluminum housing
- Premium workmanship in accordance with Waldmann's quality standards

### SPECIFICATIONS:

Voltage	100-240V
Lamping - LED	LED
Lamping - Fluorescent	T5 fluorescent
Controls	rocker switch
Color Temperature	4000K
Color Rendering Index (CRI)	80
Luminaire Head Material	anodized aluminum
Lens Material	PMMA acrylic
Luminaire Dimension	varied lengths, 7.4" width
Power Consumption	various
Protection Rating	IP20
Cord/Plug	9' w/ shock-proof plug or plug/bushing (thru-wired)
Certification	CE, ETL/cETL
Mounting	multi-dimensional T-rail brackets or C-rail brackets available
Mounting and accessories	See page 71




TAMETO is designed to offer broad, bright light output for workbenches and assembly workstations. It reduces glare, eye strain and fatigue, providing a comfortable work environment for long workdays. Strong, sleek and minimalistic, the TAMETO has a closed design suitable for cleanroom applications. Available in LED and T5 fluorescent versions, the extremely long lamp life and 60% energy savings make the TAMETO the perfect complement to a busy workplace.



Shown with T-rail bracket (included)



**DIMENSIONAL DATA**



TAMETO 900 Top Fixed Mount



TAMETO 1200 Pendant Suspended



Measurements in millimeters

**ORDERING INFORMATION**

Wattage	Light Source	Length (A)	Mounting	Lumens	Model	Part #
20W	LED	17.9" (456mm)	Side mount	1400	SAHKQ 60	112 989 000 - 006 364 07
20W	LED	25.8" (656mm)	Top fixed	1500	SAHQ 44	112 971 000 - 006 361 65
29W	LED	37.6" (956mm)	Top fixed	2400	SAHQ 66	112 975 000 - 005 556 19
38W	LED	49.5" (1256mm)	Top fixed	3200	SAHQ 88	112 979 000 - 005 556 77
29W	LED	37.6" (956mm)	Suspended	2400	SAHQ 66	112 983 000 - 006 338 60
38W	LED	49.5" (1256mm)	Suspended	3200	SAHQ 88	112 987 000 - 006 347 90
26W	T5HO fluorescent	25.8" (656mm)	Top rotating	1750	SAH 124	112 969 000 - 006 311 73
42W	T5HO fluorescent	37.6" (956mm)	Top rotating	3100	SAH 139	112 973 000 - 005 56 029
59W	T5HO fluorescent	49.5" (1256mm)	Top rotating	4450	SAH 154	112 977 000 - 005 561 83
42W	T5HO fluorescent	37.6" (956mm)	Suspended	3100	SAHZ 139	112 981 000 - 006 339 77
59W	T5HO fluorescent	49.5" (1256mm)	Suspended	4450	SAHZ 154	112 985 000 - 006 342 73

Thru-wire options available. Call for details.

Mounting Options	Item	Unit	Part #
	Mounting brackets, for use with top rotating versions	Sold as pair	408 001 586 - 005 780 88
	Adjustable mounting bracket for side mount version	Sold individually	408 001 917 - 005 612 05
	T-rail brackets (included)	Pair	N/A