



fitted with


- work equipment**
- connected load**
- power consumption**
- system of protection**
- class of protection**
- technology**
- usage**
- luminaire body**
- material
- surface
- color
- lamp cover**
- tubular sections**
- material
- surface
- color
- balance of articulation joints**
- weight (net)**
- mains lead**
- fastening**
- lens; dimensions**
- lens; diopters**
- add-on lens; dimensions**
- lens; diopters
- special features

- 48 x Light-emitting diode
- light color neutral white, 3700-4000 K, Color Rendering Index (CRI)=90
- electronic plug-in transformer
- 100-240 V; 50/60 Hz
- approx. 14 W
- IP 20
- II
- multi stage switchable; continuously dimmable
- multi-function switch

- plastic
- untreated
- black
- Acrylic satine

- tubular aluminium section
- anodized
- aluminium colored anodised
- spring
- approx. 2.7 kg (6 lbs)
- approx. 3.4 m (11 ft); US and Euro plugs incl.
- Table Clamp
- Ø 160 mm (6.3")
- 3,5
- Ø 31.5 mm (1.24")
- 8
- segment switched LED

illuminance



measuring conditions: d=15cm

E_{min}: 1377 lx
E_m: 4002 lx
E_{max}: 6141 lx

