

Dmed® triango 30 W

TECHNICAL DATA

TREATMENT LIGHTS

FITTED WITH	1 x LED lamp
LUMINOUS POWER	50 000 Lux / 1,0 m
ILLUMINANCE FIELD 1,0 M	Ø 16 cm
COLOR RENDERING INDEX (CRI)	>95
COLOUR TEMPERATUR	approx. 4500 K
WORK EQUIPMENT	electronic converter
CONNECTED LOAD	100-240 V, 50/60 Hz
MAINS LEAD	direct power supply
LUMINAIRE BODY	polycarbonate & acrylonitrile butadiene styrene copolymer (PC & ABS)
POWER CONSUMPTION	approx. 30 W
USAGE	rotary switch on the luminaire head
TECHNOLOGY	single-pole secondary, continuously dimmable
BALANCE OF ARTICULATION JOINTS	spring (weight compensation)
CLASS OF PROTECTION	I
ACCESSORY	sterilizable handle
NORMS	EN 60601-1, EN 60601-2-41
SPECIAL FEATURES	sterilisable grip, maintenance free
FASTENING	wall mount
SYSTEM OF PROTECTION	IP 43
ORDER NUMBER	D15175000 - pure white



LIGHT DISTRIBUTION

TECHNICAL DRAWING

