



NEMA 1-15P

- light source
- work equipment
- connected load
- power consumption
- luminous flux
- luminous efficiency
- light color
- color temperature
- color rendering index (CRI)
- light distribution
- direct ratio
- beam angle
- chromaticity tolerance LED
- luminance (L65)
- unified glare rating (4H 8H)
- system of protection
- class of protection
- technology
- operation
- housing
- cover
- arm
- balance of articulation joints
- weight (net)
- mains lead
- mains plug
- fastening
- decorative contrast side parts
- head length

- LED
- electronic ballast
- 100-240VAC, 50/60Hz, secondary 24V DC
- approx. 30W
- approx. 2,000 lm
- approx. 76 lm/W
- cold white
- approx. 5,000K
- CRI ≥ 90; R9 ≥ 50
- direct
- approx. 100%
- 110°
- < 3 SDCM
- ≤ 23,000 cd/m²
- ≤ 28
- IP 20
- I with plug-in power supply:
- III without plug-in power supply
- touch DIM
- multi-function switch
- white
- milky; plastic
- white
- spring
- approx. 5.1 lb (2.3 kg)
- approx. 11.1 ft (3.4m)
- US, UK, Euro, and Swiss
- table base
- black
- 22.7" (577 mm)

light distribution

