



**fitted with**

- work equipment**
- connected load**
- power consumption**
- system of protection**
- class of protection**
- technology**
- usage**
- luminaire body**
- material
- surface
- lamp cover**
- tubular sections**
- material
- surface
- balance of articulation joints**
- weight (net)**
- mains lead**

- 48 x Light-emitting diode
- neutral white, 3700-4200 K
- Color Rendering Index (CRI)=90
- electronic plug-in ballast
- 100-240V; 50/60 Hz
- approx. 14 W
- IP 20
- II
- multi-stage switchable, continuously dimmable
- multi-function switch

- plastic
- ESD-version
- screen, milky, Polyamide

- tubular aluminum section
- ESD-coat of lacquer
- spring
- approx. 5.7 lb. (2.6 kg)
- approx. 11.8 ft. (3.6 m); NEMA 1-15P plug

- fastening**
- lens; dimensions**
- lens material**
- lens; diopters**
- add-on lens; dimensions**
- special features**

- screw-down flange
- Ø 6.3 in. (160 mm)
- glass
- 3.5
- not available
- light characteristic can be adjusted with a three-way switch



NEMA 1-15P

**illuminance**

measuring conditions: d=15cm

**Em:** 3089 lx  
**Emax:** 4636 lx  
**Emin:** 1013 lx

