



fitted with

- work equipment
- connected load
- power consumption
- luminous flux
- luminous efficacy
- illuminance efficiency factor
- light colour
- color rendering index (CRI)
- consistent white light of glare-free
- class of protection
- technology
- luminaire body
- lamp cover
- tubular sections
- balance of articulation joints
- weight (net)
- mains lead

fastening

special features

LED

Energy efficiency category A+

electronic plug-in transformer

100-240 V; 50/60 Hz

approx. 8 W

approx. 530 lm

approx. 66 lm/W

101 lx/W

warm white, approx. 3000 K

> 90 (R9>50)

< 4 SDCM

plastic reflector

II with plug-in power supply

continuously dimmable

aluminium, painted, silver

screen, clear

tubular aluminium section, painted, silver

friction

approx. 1.0 kg (2.2 lb)

approx. 3 m (9.84 ft); mains plug

US~ConnectionStandard

adaptor (accessory), table base (accessory), table clamp (accessory)

automatic switchoff adjustable, push button in luminaire head, behaviour at net recovery adjustable




\*Separate ENEC certification for luminaire and power supply



NEMA 1-15P

illuminance

distance: 50 cm  
 Em: 750 lx  
 Emax: 1127 lx  
 Emin: 414 lx



luminous intensity

