



fitted with

- work equipment
- connected load
- power consumption
- luminous flux
- luminous efficacy
- illuminance efficiency factor
- light colour
- color rendering index (CRI)
- consistent white light of glare-free
- class of protection
- technology
- luminaire body
- lamp cover
- tubular sections
- balance of articulation joints
- weight (net)
- mains lead

fastening

special features

LED

Energy efficiency category A+
 electronic plug-in transformer
 100-240 V; 50/60 Hz
 approx. 8 W
 approx. 550 lm
 approx. 68 lm/W
 101 lx/W
 neutral white, approx. 4000 K
 > 90 (R9>50)
 < 4 SDCM
 plastic reflector
 II with plug-in power supply
 continuously dimmable
 aluminium, painted, red
 screen, clear
 tubular aluminium section, painted, red
 friction
 approx. 1.0 kg (2.2 lb)
 approx. 3 m (9.84 ft); mains plug
 US~ConnectionStandard
 adaptor (accessory), table base (accessory), table
 clamp (accessory)
 automatic switchoff adjustable, push button in
 luminaire head, behaviour at net recovery
 adjustable




* Separate ENEC certification for luminaire and power supply



NEMA 1-15P

illuminance

distance: 50 cm
 Em: 775 lx
 Emax: 1166 lx
 Emin: 430 lx



luminous intensity

