



- fitted with
- work equipment
- connected load
- power consumption
- luminous flux
- luminous efficacy
- illuminance efficiency factor
- light colour
- color rendering index (CRI)
- consistent white light of
- glare-free
- class of protection
- technology
- luminaire body
- lamp cover
- tubular sections
- balance of articulation joints
- weight (net)
- mains lead
- fastening
- special features

- LED
- Energy efficiency category A+
- electronic plug-in transformer
- 100-240 V; 50/60 Hz
- approx. 8 W
- approx. 550 lm
- approx. 68 lm/W
- 102 lx/W
- neutral white, approx. 4000 K
- > 90 (R9>50)
- < 4 SDCM
- plastic reflector
- II with plug-in power supply
- continuously dimmable
- aluminium, painted, black
- screen, clear
- tubular aluminium section, painted, black
- friction
- approx. 1.0 kg (2.2 lb)
- approx. 3 m (9.84 ft); mains plug
- US-ConnectionStandard
- adaptor (accessory), table base (accessory), table clamp (accessory)
- automatic switchoff adjustable, push button in luminaire head, behaviour at net recovery adjustable




* Separate ENEC certification for luminaire and power supply



NEMA 1-15P

illuminance

distance: 50 cm
 Em: 775 lx
 Emax: 1166 lx
 Emin: 430 lx



luminous intensity

