



fitted with

- work equipment
- connected load
- power consumption
- luminous flux
- luminous efficacy
- illuminance efficiency factor
- light colour
- color rendering index (CRI)
- consistent white light of glare-free
- class of protection
- technology
- luminaire body
- lamp cover
- tubular sections
- balance of articulation joints
- weight (net)
- mains lead

fastening

special features

LED

Energy efficiency category A+  
 electronic plug-in transformer  
 100-240 V; 50/60 Hz  
 approx. 8 W  
 approx. 550 lm  
 approx. 68 lm/W  
 102 lx/W  
 neutral white, approx. 4000 K  
 > 90 (R9>50)  
 < 4 SDCM  
 plastic reflector  
 II with plug-in power supply  
 continuously dimmable  
 aluminium, painted, red  
 screen, clear  
 tubular aluminium section, painted, red  
 friction  
 approx. 1.0 kg (2.2 lb)  
 approx. 3 m (9.84 ft); mains plug  
 US-ConnectionStandard  
 adaptor (accessory), table base (accessory), table  
 clamp (accessory)  
 automatic switchoff adjustable, push button in  
 luminaire head, behaviour at net recovery  
 adjustable




\* Separate ENEC certification for luminaire and power supply



NEMA 1-15P

illuminance

distance: 50 cm  
 Em: 775 lx  
 Emax: 1166 lx  
 Emin: 430 lx



luminous intensity

