



fitted with

work equipment  
connected load  
power consumption  
luminous flux  
luminous efficacy  
illuminance efficiency factor  
light colour  
color rendering index (CRI)  
consistent white light of  
glare-free  
class of protection  
technology  
luminaire body  
lamp cover  
tubular sections  
balance of articulation joints  
weight (net)  
mains lead

fastening

special features

LED  
Energy efficiency category A+  
electronic plug-in transformer  
100-240 V; 50/60 Hz  
approx. 8 W  
approx. 530 lm  
approx. 66 lm/W  
88 lx/W  
warm white, approx. 3000 K  
> 90 (R9>50)  
< 4 SDCM  
plastic reflector  
II with plug-in power supply  
continuously dimmable  
aluminium, painted, black  
screen, clear  
tubular aluminium section, painted, black  
friction  
approx. 0.5 kg (1.1 lb)  
approx. 3 m (9.84 ft); mains plug  
US~ConnectionStandard  
adaptor (accessory), table base (accessory), table  
clamp (accessory)  
automatic switchoff adjustable, push button in  
luminaire head, behaviour at net recovery  
adjustable




\* Separate ENEC certification for luminaire and power supply



NEMA 1-15P

illuminance

distance: 50 cm  
Em: 750 lx  
E<sub>max</sub>: 1127 lx  
E<sub>min</sub>: 414 lx



luminous intensity

