



fitted with

work equipment  
connected load  
power consumption  
luminous flux  
luminous efficacy  
Illuminance efficiency factor  
light colour  
color rendering index (CRI)  
consistent white light of  
glare-free  
class of protection  
technology  
luminaire body  
lamp cover  
tubular sections  
balance of articulation joints  
weight (net)  
mains lead

fastening

special features

LED

Energy efficiency category A+  
electronic plug-in transformer  
100-240 V; 50/60 Hz  
approx. 8 W  
approx. 530 lm  
approx. 66 lm/W  
92 lx/W  
warm white, approx. 3000 K  
> 90 (R9>50)  
< 4 SDCM  
plastic reflector  
II with plug-in power supply  
continuously dimmable  
aluminium, painted, white  
screen, clear  
tubular aluminium section, painted, white  
friction  
approx. 0.5 kg (1.1 lb)  
approx. 3 m (9.84 ft); mains plug  
US~ConnectionStandard  
adaptor (accessory), table base (accessory), table  
clamp (accessory)  
automatic switchoff adjustable, push button in  
luminaire head, behaviour at net recovery  
adjustable




Separate ENEC certification for luminaire and power supply



NEMA 1-15P

illuminance

distance: 50 cm  
Em: 750 lx  
E<sub>max</sub>: 1127 lx  
E<sub>min</sub>: 414 lx



luminous intensity

