

# High bay luminaire

ACANEO - HIAL 30000/840/N/1-10V 113239000 00682497

# Waldmann **W**

ENGINEER OF LIGHT.



fitted with

LED

work equipment  
connected load  
power consumption  
power factor  
lens  
luminous flux  
luminous efficacy  
beam angle  
light color  
color rendering index (CRI)  
consistent white light of unified  
glare rating  
system of protection  
class of protection  
technology  
luminaire body  
lamp cover  
weight (net)  
mains lead  
fastening  
minimum ambient temperature  
maximum ambient temperature  
Overvoltage resistance Impact  
strength life

dimmable electronic driver; 1-10V  
120-277V; 50/60Hz  
approx. 230 W  
approx. 0,950  
N optics; narrow beam  
approx. 30000 lm  
approx. 130 lm/W  
55  
neutral white, approx. 4000 K  
> 80  
< 3 SDCM  
< 20  
IP 65  
I  
continuously dimmable  
aluminium, powder-coated  
acrylic clear  
approx. 10.8 kg (23.8 lbs)  
approx. 4m (13 ft); free stranded wires  
optional mounting brackets  
-30 °C (-22 F)  
+50 °C (122 F)  
>= 4000 V  
IK08 (IK10 with safety glass)  
L80B10 after 60;000 h (according to IES  
LM 80 and TM 21-11)

## luminous intensity

