

# High bay luminaire

ACANEO - HIAL 30000/850/W/EA 113443000 00693069

# Waldmann **W**

ENGINEER OF LIGHT.



## fitted with

work equipment  
connected load  
power consumption  
power factor  
lens  
luminous flux  
luminous efficacy  
beam angle  
light color  
color rendering index (CRI)  
consistent white light of unified  
glare rating  
system of protection  
class of protection  
technology  
luminaire body  
lamp cover  
weight (net)  
mains lead  
fastening  
minimum ambient temperature  
maximum ambient  
temperature Overvoltage  
resistance Impact strength  
life

## LED

electronic ballast  
120-277V; 50/60Hz  
approx. 230 W  
approx. 0,950  
W optics; wide beam  
approx. 30000 lm  
approx. 130 lm/W  
85  
neutral white, approx. 5000 K  
> 80  
< 3 SDCM  
< 22  
IP 65  
I  
switchable  
aluminium, powder-coated,  
acrylic clear  
approx. 10.8 kg (23.8 lbs)  
approx. 4m (13 ft); free stranded leads  
optional mounting brackets  
-30 °C (-22 F)  
+50 °C (122 F)  
>= 4000 V  
IK08 (IK10 with safety glass)  
L80B10 after 60;000 h (according to IES LM 80  
and TM 21-11)

## luminous intensity

