



fitted with

- work equipment
- connected load
- power consumption
- standby
- power factor
- luminous flux
- luminous efficacy
- light distribution
- direct ratio
- light color
- color rendering index (CRI)
- consistent white light of
- glare-free
- luminance
- unified glare rating
- system of protection
- technology
- usage
- luminaire body
- lamp cover
- weight (net)
- mains supply
- fastening
- special features

LED

- electronic ballast, 0-10V
- 120-277V; 50/60Hz
- approx. 49 W
- approx. 0.30 W
- approx. 0.950
- approx. 7000 lm
- approx. 143 lm/W
- direct/indirect
- approx. 34 %
- neutral white, approx. 4000 K
- > 80
- < 3 SDCM
- conical prismatic screen
- < 2500 cd/m²
- < 16
- IP 20
- 0-10V, 1% continuously dimmable
- external
- white
- acrylic clear
- approx. 7.5 kg (16.5 lbs)
- connector
- steel cable 0.3 - 0.7 m (1 - 2.3 ft)
- down light edge lit, indirect light with bat wing distribution, 0-10V dimming, single circuit, UL approved, end fixture

dimensions in mm

- 20 mm = 0.787 in
- 30 mm = 1.181 in
- 250 mm = 9.843 in
- 300 mm = 11.811 in
- 700 mm = 27.559 in
- 1200 mm = 47.244 in
- 1207 mm = 47.520 in
- 1230 mm = 48.425 in

luminous intensity

