



|                             |   |
|-----------------------------|---|
| fitted with                 | LED                                     |
| work equipment              | Energy efficiency category A+           |
| connected load              | electronic ballast                      |
| power consumption           | 120-277V; 50/60Hz                       |
| standby                     | approx. 19 W                            |
| power factor                | approx. 0,15 W                          |
| luminous flux               | approx. 0,960                           |
| luminous efficacy           | approx. 2300 lm                         |
| light distribution          | approx. 121 lm/W                        |
| direct ratio                | direct/indirect                         |
| light colour                | approx. 40 %                            |
| color rendering index (CRI) | neutral white, approx. 4000 K           |
| consistent white light of   | > 80                                    |
| glare-free                  | < 3 SDCM                                |
| luminance                   | conical prismatic screen                |
| unified glare rating        | < 2600 cd/m <sup>2</sup>                |
| system of protection        | < 16                                    |
| technology                  | IP 40                                   |
| usage                       | 0 - 10 dimming                          |
| luminaire body              | external                                |
| lamp cover                  | sectional aluminium, white              |
| weight (net)                | acrylic clear                           |
| mains lead                  | approx. 3.3 kg, 7.27 lb                 |
| fastening                   | approx. 1,0 m; with free stranded wires |
| dimension                   | steel cable 0.3 - 0.7 m, 1 - 2.3 ft     |
|                             | L=854mm, 2.8 ft                         |



luminous intensity

