



<p>fitted with</p> <p>work equipment</p> <p>connected load</p> <p>power consumption</p> <p>standby</p> <p>power factor</p> <p>luminous flux</p> <p>luminous efficacy</p> <p>light distribution</p> <p>direct ratio</p> <p>light colour</p> <p>color rendering index (CRI)</p> <p>consistent white light of</p> <p>glare-free</p> <p>luminance</p> <p>unified glare rating</p> <p>system of protection</p> <p>technology</p> <p>usage</p> <p>luminaire body</p> <p>lamp cover</p> <p>weight (net)</p> <p>mains lead</p> <p>fastening</p> <p>dimension</p>	<p>LED</p> <p>Energy efficiency category A+</p> <p>electronic ballast</p> <p>120-277V; 50/60Hz</p> <p>approx. 51 W</p> <p>approx. 0,15 W</p> <p>approx. 0,980</p> <p>approx. 6200 lm</p> <p>approx. 122 lm/W</p> <p>direct/indirect</p> <p>approx. 40 %</p> <p>neutral white, approx. 4000 K</p> <p>> 80</p> <p>< 3 SDCM</p> <p>conical prismatic screen</p> <p>< 2600 cd/m²</p> <p>< 16</p> <p>IP 40</p> <p>0 - 10 dimming</p> <p>external</p> <p>sectional aluminium, white</p> <p>acrylic clear</p> <p>approx. 7.5 kg, 16.53 lb</p> <p>approx. 1,0 m, 3.28 ft; with free stranded wires</p> <p>steel cable 0.3 - 0.7 m, 1 - 2.3 ft</p> <p>L=2250mm, 7.38 ft</p>
--	---



luminous intensity

