



fitted with

work equipment  
 connected load  
 power consumption  
 standby  
 power factor  
 luminous flux  
 luminous efficacy  
 light distribution  
 direct ratio  
 light colour  
 color rendering index (CRI)  
 consistent white light of  
 glare-free  
 luminance  
 unified glare rating  
 system of protection  
 technology  
 usage  
 luminaire body  
 lamp cover  
 weight (net)  
 mains lead  
 fastening  
 dimension

LED

Energy efficiency category A+  
 electronic ballast  
 120-277V; 50/60Hz  
 approx. 51 W  
 approx. 0,15 W  
 approx. 0,980  
 approx. 6200 lm  
 approx. 122 lm/W  
 direct/indirect  
 approx. 40 %  
 neutral white, approx. 4000 K  
 > 80  
 < 3 SDCM  
 conical prismatic screen  
 < 2600 cd/m<sup>2</sup>  
 < 16  
 IP 40  
 0 - 10 dimming  
 external  
 sectional aluminium, silver  
 acrylic clear  
 approx. 7.5 kg, 16.53 lb  
 approx. 1,0 m, 3.28 ft; with free stranded wires  
 steel cable 0.3 - 0.7 m, 1 - 2.3 ft  
 L=2250mm, 7.38 ft



luminous intensity

