



light source

work equipment
connected load
Power consumption
luminous efficacy
colour temperature
color rendering index (CRI)
chromaticity tolerance LED
System of protection
class of protection
technology
operation
luminaire body
lamp cover
tubular sections

balance of articulation joints
weight (net)
mains lead

Fastening
lens; dimensions
lens material
lens; diopters
special features

LED

Energy efficiency category A/A+/A++
electronic plug-in ballast
100-240 V; 50/60 Hz
approx. 13 W
approx. 57 lm/W
neutral white, approx. 5000 K
>= 90 (R9>50)
3 SDCM
IP20
II
multi-stage switchable, continuously dimmable
multi-function switch
plastic, untreated, black
screen, milky, Polyamide
tubular aluminium section, anodized, aluminium coloured
anodised
spring
approx. 2.5 kg (5.51 lb)
approx. 3.6 m (11.81 in); mains plug
BS 1363
CEE 7/XVI
NEMA 1-15P
screw-down flange
Ø 160 mm (6.29 in)
glass
3,5
light characteristic can be adjusted with a three-way switch,
arm length 31"



BS 1363



CEE 7/XVI



NEMA 1-15P

illuminance

distance: 15 cm

Em: 4099 lx
E_{max}: 5537 lx
E_{min}: 1894 lx

