



light source

work equipment  
connected load  
Power consumption  
luminous efficacy  
colour temperature  
color rendering index (CRI)  
chromaticity tolerance LED  
System of protection  
class of protection  
technology  
operation  
luminaire body  
lamp cover  
tubular sections

balance of articulation joints  
weight (net)  
mains lead

Fastening  
lens; dimensions  
lens material  
lens; diopters  
add-on lens; dimensions  
add-on lens; diopters  
special features

LED

Energy efficiency category A/A+/A++  
electronic plug-in ballast  
100-240 V; 50/60 Hz  
approx. 13 W  
approx. 57 lm/W  
neutral white, approx. 5000 K  
>= 90 (R9>50)  
3 SDCM  
IP20  
II  
multi-stage switchable, continuously dimmable  
multi-function switch  
plastic, untreated, black  
screen, milky, Polyamide  
tubular aluminium section, anodized, aluminium coloured  
anodised  
spring  
approx. 3.0 kg (6.61 lb)  
approx. 3.4 m (11.5 in); mains plug  
BS 1363  
CEE 7/XVI  
NEMA 1-15P  
screw-down flange  
Ø 160 mm (6.29 in)  
glass  
3,5  
Ø 31.5 mm (1.24 in)  
8  
adhesive add-on magnifier, long arms, light characteristic  
can be adjusted with a three-way switch,  
arm length 39"



BS 1363



CEE 7/XVI



NEMA 1-15P

illuminance

distance: 15 cm

Em: 4099 lx  
E<sub>max</sub>: 5537 lx  
E<sub>min</sub>: 1894 lx

