




<b>fitted with</b>	LED
<b>work equipment</b>	electronic driver
<b>connected load</b>	120-277V; 50/60Hz
<b>power consumption</b>	approx. 16 W
<b>standby</b>	approx. 0.20 W
<b>power factor</b>	approx. 0.970
<b>luminous flux</b>	approx. 1350 lm
<b>luminous efficacy</b>	approx. 84 lm/W
<b>light distribution</b>	direct
<b>direct ratio</b>	approx. 100 %
<b>light color</b>	neutral white, approx. 4000 K
<b>color rendering index (CRI)</b>	> 80
<b>consistent white light of</b>	< 3 SDCM
<b>glare-free</b>	conical prismatic screen
<b>luminance</b>	< 3000 cd/m <sup>2</sup>
<b>unified glare rating</b>	< 19
<b>system of protection</b>	IP 40
<b>technology</b>	0-10V continuously dimmable to 1%
<b>usage</b>	external
<b>luminaire body</b>	sectional aluminium, white
<b>lamp cover</b>	acrylic clear
<b>weight (net)</b>	approx. 3.9 kg (8.6 lbs)
<b>mains lead</b>	approx. 3.0 m (9.8 ft); with free stranded wires
<b>fastening</b>	steel cable 0.3 - 3.0 m (1.0 - 9.8 ft)
<b>dimension</b>	L=1122mm (3.68 ft)
<b>special features</b>	mounting and canopies included



**luminous intensity**



dimension in mm

