




|                                    |   |
|------------------------------------|---|
| <b>fitted with</b>                 | LED   |
| <b>work equipment</b>              | electronic driver                               |
| <b>connected load</b>              | 120-277VV; 50/60Hz                              |
| <b>power consumption</b>           | approx. 30 W                                    |
| <b>standby</b>                     | approx. 0.15 W                                  |
| <b>power factor</b>                | approx. 0.960                                   |
| <b>luminous flux</b>               | approx. 2700 lm                                 |
| <b>luminous efficacy</b>           | approx. 90 lm/W                                 |
| <b>light distribution</b>          | direct  |
| <b>direct ratio</b>                | approx. 100 %                                   |
| <b>light color</b>                 | neutral white, approx. 4000 K                   |
| <b>color rendering index (CRI)</b> | > 80  |
| <b>consistent white light of</b>   | < 3 SDCM  |
| <b>glare-free</b>                  | conical prismatic screen                        |
| <b>luminance</b>                   | < 3000 cd/m <sup>2</sup>                        |
| <b>unified glare rating</b>        | < 19  |
| <b>system of protection</b>        | IP 40   |
| <b>technology</b>                  | 0-10V continuously dimmable to 1%               |
| <b>usage</b>                       | external controls                               |
| <b>luminaire body</b>              | sectional aluminium, white                      |
| <b>lamp cover</b>                  | acrylic clear                                   |
| <b>weight (net)</b>                | approx. 7.3 kg (16.09 lbs)                      |
| <b>mains lead</b>                  | approx. 3.0 m (9.8ft); with free stranded wires |
| <b>fastening</b>                   | steel cable 0.3 - 3.0 m (1.0 - 9.8 ft)          |
| <b>dimension</b>                   | L=2244mm (7.36 ft)                              |
| <b>special features</b>            | mounting and canopies included                  |



**luminous intensity**



dimensions in mm

