

# Surface-mounted luminaire ACURIA.perfect APA 2000/850/MS

114314000-00806633

# Waldmann **W**

ENGINEER OF LIGHT.



**light source**  
**work equipment**  
**connected load**  
**power consumption**  
**luminous flux**  
**luminous efficiency**  
**light distribution**  
**beam angle**  
**color temperature**  
**color temperature**  
**color rendering index (CRI)**  
**chromaticity tolerance LED**  
**glare control**  
**luminance (L65)**  
**unified glare rating (4H 8H)**  
**technology**  
**operation**  
**housing**  
  
**cover**  
**weight (net)**  
**mains lead**  
**fastening**  
**dimension**  
**special features**

LED  
without  
24 V, DC  
env. 14 W  
approx. 1900 lm  
approx. 136 lm/W  
direct  
92°  
neutral white  
approx. 5,000 K  
>= 80  
< 3 SDCM  
screen  
<= 4200 cd/m<sup>2</sup>  
<= 22  
multi-stage switchable  
external  
aluminum; anodized; aluminum  
colored anodized  
glass screen  
env. 1.40 kg (3.09 lbs)  
built-in plug; M12-A-5  
snap-fit  
A=215 mm (8.46")  
ADVANCED package



## light distribution

