




Light source	LED
Work equipment	Without
Connected load	22 - 26 V; DC
Power consumption	approx. 16 W
Luminous flux	approx. 1,450 lm
Luminous efficiency ¹⁾	approx. 90 lm/W
Light type/-color	Cold white
Color temperature	approx. 5,000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct; approx. 100 %
Beam angle	110 °
Chromaticity tolerance LED	< 4 SDCM
Glare control	Diffusor
Luminance (L65)	≤ 23,000 cd/m ²
UGRclass (4H 8H; EN 12464-1)	≤ 28
System of protection/Class	IP 65; III
Technology	Switchable; Continuously dimmable
Operation	Push button
Housing	Aluminum; Painted; Jet black
Light source cover	Polycarbonate (PC); White opal
Arm	Tubular aluminum section; Anodized; Black
Balance of articulation joints	Spring
Mains lead	approx. 9.8ft (3 m); With free stranded wires
Fastening	Table clamp (accessory); Wall bracket (accessory); Screw-down flange
Weight without/incl. packaging	approx. 3.7 lbs (1.7 kg)
Special features	Fully spring-relieved arm



¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear

