



|                                |  |
|--------------------------------|--|
| fitted with                    | 2 x LED module indirect<br>2 x LED module direct<br>power supply unit<br>120V; 50/60Hz<br>approx. 81W<br>approx. 0,988<br>approx. 10000 lm<br>approx. 120 lm/W<br>direct/indirect<br>approx. 28 %<br>neutral white, approx. 4000 K<br>> 80<br>< 3 SDCM<br>conical prismatic screen<br>< 2500 cd/m <sup>2</sup><br>< 16<br>on/off - dimmable<br>multi-function switch<br>steel/plastic, painted, white<br>acrylic clear<br>steel tube, painted, tubular section upright, white<br>C-form flat<br>approx. 18.5 kg (41 lbs)<br>approx. 3,0 m (9.84 ft); 3 prong plug<br>NEMA 5-15<br>floor standing base<br>flint grey<br>luminaire head detachable |
| work equipment                 |  |
| connected load                 |  |
| power consumption              |  |
| power factor                   |  |
| luminous flux                  |  |
| light yield                    |  |
| light distribution             |  |
| direct ratio                   |  |
| light colour                   |  |
| Color Rendering Index (CRI)    |  |
| consistent white light of      |  |
| glare-free                     |  |
| luminance                      |  |
| unified glare rating           |  |
| technology                     |  |
| usage                          |  |
| luminaire body                 |  |
| lamp cover                     |  |
| tubular section                |  |
| luminaire base                 |  |
| weight (net)                   |  |
| mains lead                     |  |
| fastening                      |  |
| decorative contrast side parts |  |
| special features               |  |



luminous intensity

