



Light source	LED
Work equipment	electronic ballast DALI
Connected load	120 VAC; 50/60 Hz
Power consumption	approx. 85 W
Luminous flux	approx. 12,500 lm
Luminous efficiency	approx. 145 lm/W
Light type/-color	cold white
Color temperature	approx. 4,000 K
Color rendering index	CRI ≥ 80
Light distribution	direct/indirect; approx. 17 % direct
Chromaticity tolerance LED	< 3 SDCM
Glare control	prism aperture
Luminance (L65)	≤ 3,000 cd/m <sup>2</sup>
UGRclass (4H 8H; EN 12464-1)	≤ 16
System of protection/Class	IP 20; I
Technology	presence and daylight sensor control (PIR)
Operation	rocker switch, dimmable
Housing	steel/plastic; painted; black
Light source cover	polycarbonate (PC); Clear
Arm	steel tube; painted; tubular section upright; black
Mains lead	approx. 3.7 m (12.1 ft); NEMA 5-15P
Fastening	socket; table adaptor
Decorative contrast side parts	flint grey
Life expectancy LED	L80B50 50,000h
Energy efficiency class	C
Weight	approx. 8.3 kg (18.3 lbs)
Special features	Integrated light and presence sensor PIR; Flicker-free; Motion sensor time-out of 15mins~; Luminaire head detachable; Direct and indirect light switchable together

