

## SUBMITTAL SHEET

STARLINE™ ASTERISK

**CLIENT**

**PROJECT NAME**

**FIXTURE TYPE**

**QUANTITY**



<b>fitted with</b>	LED w/ STARLINE micro downlight reflectors
<b>work equipment</b>	electronic driver
<b>connected load</b>	100-277 V;50/60 Hz
<b>power consumption</b>	approx. 27 W
<b>luminous flux</b>	approx. 3500 lm
<b>luminous efficacy</b>	approx. 125 lm/W
<b>light distribution</b>	direct
<b>direct ratio</b>	approx. 100 %
<b>beam angle</b>	75°
<b>light color temperature</b>	3000K, 3500K, 4000K, (2700-6500K Tunable)
<b>color rendering index (CRI)</b>	> 80
<b>glare-free (UGR)</b>	<13
<b>system of protection</b>	IP 20
<b>technology</b>	controls compatible
<b>usage</b>	direct connect
<b>luminaire body</b>	metal steel sheet, powder coated: black, white, or gray
<b>weight (net)</b>	approx. 4.3 kg (9.47 lbs)
<b>special features</b>	STARLINE OPTICS micro downlight reflector allows precise shaping of light beam. Thin design for ceiling constraints fits standard drop ceilings.

For ordering information or installation instructions visit: [www.waldmannlighting.com/products/asterisk](http://www.waldmannlighting.com/products/asterisk)

## ORDER CONFIGURATION

<b>D</b>	-	<b>O</b>	-	<b>A</b>	-	-	-	<b>0</b>
<b>Direct</b>		<b>Only</b>		<b>Asterisk</b>				<b>Variants</b>
				<b>Color Temperature</b>		<b>Surface Color</b>		<b>Power Supply</b>
				30 - 3000K		B: Black		A0: 0-10V Dimming
				35 - 3500K		W: White		L1: Lutron LDE1
				40 - 4000K		G: Gray		L5: Lutron LDE5
				65 - 2700 - 6500K Tunable				DS: DALI Dimming (Single Color) *
								DD: DALI Dimming (Tunable)
								CS: Molex CoreSync

Waldmann Lighting Company  
9 Century Dr. Wheeling, IL 60090

Telephone (847) 520 1060  
Fax (847) 520 1730

[www.waldmannlighting.com](http://www.waldmannlighting.com)  
[waldmann@waldmannlighting.com](mailto:waldmann@waldmannlighting.com)