

TECHNICAL DATA TREATMENT LIGHTS

| | |
|---------------------------|--|
| FITTED WITH | 2 x halogen lamp QT12 50 W - D68615000 |
| LUMINOUS POWER | 2 x 54000 Lux / 0,8 m (31.5") 2 x 42000 Lux / 1,0 m (39.4") |
| ILLUMINANCEFIELD 0,8 M | Ø 15 cm (5.9") |
| COLOUR TEMPERATURE | approx. 4300 K |
| WORK EQUIPMENT | electronic transformer |
| CONNECTED LOAD | 120 V; 60 Hz |
| MAINS LEAD | direct power supply |
| LUMINAIRE BODY | polyamide & polycarbonate (PA & PC) |
| WEIGHT (NET) | approx. 26,0 kg (57.3 lbs) |
| POWER CONSUMPTION | approx. 130 W |
| USAGE | rocker switch (I/O), 2-stages rocker switch (60/100 %) |
| TECHNOLOGY | 2-pole primary, single switchable |
| CLASS OF PROTECTION | II |
| NORMS | EN 60601-1, EN 60601-2-41 |
| SPECIAL FEATURES | colour correction filter (4300 K), sterilisable grip |
| FASTENING | ceiling mount 119cm (47")*, intermediate ceiling adapter (on request) <small>*includes 3" for double connection piece</small> |





| H1 Height of room (cm) | H2 Headroom, horizontal arm (cm)* | | | | | | | H3 Ceiling clearance |
|---------------------------|-----------------------------------|-----|-----|-----|-----|-----|-----|----------------------|
| | 150 | 160 | 170 | 180 | 190 | 200 | 210 | 110 cm |
| 200 | | | ● | | | | | |
| 210 | | | | ● | | | | |
| 220 | | | | | ● | | | |
| 230 | | | | | | ● | | |
| 240 | | | | | | | ● | |
| 250 | | | | | | | | |
| 260 | | | | | | | | |
| 270 | | | | | | | | |
| 280 | | | | | | | | |
| 290 | | | | | | | | |
| 300 | | | | | | | | |

* Light emission surface from this measure:
+56 cm highest position
-64 cm lowest position

Recommended distance from the light head to the work surface = 0.8 m

LIGHT DISTRIBUTION TECHNICAL DRAWING

measuring distance 0.8 m (31.5")



Dimensions in cm.

