



PROJECT:		TYPE:		QUANTITY	
-----------------	--	--------------	--	-----------------	--

Electrical:	
Nominal input voltage	100-240V
Frequency range	50 / 60Hz
Power consumption	30W (42-52VA)
Input current	0.42A
Integrated electronic transformer	24V DC output
Approval - Safety	ETL/cETL
User interface	Continuously dimmable rotary switch on the head On/off foot switch



Illumination:	
Fitted with	LED Technology
Central illuminance at 1.0m	60,000 lux
Light field diameter d10 at 1.0m	Ø = 16 cm (6.3in)
Light field diameter d50 at 1.0m	Ø = 8.5 cm (3.3in)
Depth of illumination L1 + L2	120cm (47.24in)
Color Temperature	4500 K
Color Rendering Index Ra	>95
Life time	40000h



Weight:	
Light head	3 kg (6.6lbs)
triango 30 F (includes light head)	14 kg (31lbs)
Luminaire Materials	Head – polycarbonate & acrylonitrile butadiene styrene copolymer (PC &ABS); Arm – metal

Classification:	
triango 30	Class I; FDA Class I
Degree of protection as per IEC 529	IP 20
Light head	IP 43 (horizontal position)
Electrical safety test according to:	AAMI ES60601-1, CSA C22.2#60601-1, IEC/EN 60601-1, IEC/EN 60601-2-41, IEC/EN 60601-1-2
Special feature	Removable Sterilizable Handle included

Component List - Included

#	Part Number	Description
1	D15-312-000	Head, Triango 30, 24V, LED
2	US4-001-034	Spring Balanced Arm
3	US0-241-053	Handle with screws, Gray
4	Call Factory	Base
5	US4-001-430	Locking Casters Set with pin, (4x)
6	309-593-M40	Fuses (2), 1.25A, 250v
7	US0-241-053	Power Cable
Additional Information Available (Manuals)		
1	Included	Triango Manual
2	Call Factory	Triango Spare Parts Manual

