



|                                       |                                   |
|---------------------------------------|-----------------------------------|
| <b>fitted with</b>                    | 1 x LED module                    |
| <b>luminous power</b>                 | 40 000 Lux / 0,5 m                |
| <b>Illuminancefield 0,5 m</b>         | Ø 18 cm (7.1")                    |
| <b>Color Rendering Index (CRI)</b>    | > 93                              |
| <b>colour temperatur</b>              | 4400 K                            |
| <b>work equipment</b>                 | electronic converter              |
| <b>connected load</b>                 | 120V; 50/60Hz                     |
| <b>mains lead</b>                     | 1,8 m (5.9ft) Hospital Grade Plug |
| <b>luminaire body</b>                 | polycarbonate (PC)                |
| <b>weight (net)</b>                   | 1.4 kg (3.1 lbs)                  |
| <b>power consumption</b>              | 13 W                              |
| <b>usage</b>                          | rocker switch (I/O) at the arm    |
| <b>balance of articulation joints</b> | friction                          |
| <b>class of protection</b>            | II                                |
| <b>accessory</b>                      | included wall mount bracket       |
| <br>                                  |                                   |
| <b>norms</b>                          | EN 60601-1, EN 60601-2-41         |
| <b>special features</b>               | switchable, maintenance free      |
| <b>safety</b>                         | ETL/cETL                          |
| <b>order number</b>                   | D15507120 - pure white            |

### light distribution

measuring distance 0.5 m

