

Suspended luminaire

VIVAA C 600 D15515VTL

Waldmann **W**

ENGINEER OF LIGHT.



Derungs 
LIGHT FOR PEOPLE

| | |
|------------------------------|---|
| fitted with | 6 x LED module |
| light distribution | 40% direct / 60% indirect |
| Color Rendering (CRI) | > 80 |
| color temperature | 3000 - 6500K |
| work equipment | dual circuit, DALI converters |
| connected load | 120-277V; 50/60Hz |
| mains lead | direct power supply |
| luminaire body | stainless steel |
| weight (net) | 8.1 kg (17.9 lbs) |
| power consumption | 70 W |
| luminous flux | 7000 lumens |
| lamp cover | CDP micro prism (PMMA) |
| class of protection | I |
| accessory | light diffusing foil |
| norms | EN 60598-1, EN 60598-2-25, ETL/cETL |
| room height | ceiling drop 50 cm (1.6 ft) |
| special features | Suitable for screen work according to EN 12464-1, CDP micro prismatic screen, Suitable for emergency lighting units according to EN 50172 |
| fastening | ceiling fastening (pendant) |
| system of protection | IP 20 |
| order number | D15515VTL - Stainless steel/pure white |

Compatible with DALI protocol control systems. Controls and programming supplied by other. Consult factory for program parameters.

light distribution

