



<b>fitted with</b>	1 x LED module
<b>luminous power</b>	50'000 Lux / 1,0 m
<b>illuminancefield 1,0 m</b>	Ø 17 cm (6.7")
<b>Color Rendering Index (CRI)</b>	> 95
<b>colour temperatur</b>	4300 K
<b>Depth of illumination L1+L2</b>	1,47 m (4.8 ft)
<b>work equipment</b>	electronic converter
<b>connected load</b>	120V;50/60Hz
<b>mains lead</b>	direct power supply
<b>luminaire body</b>	polycarbonate & acrylonitrile butadiene styrene copolymer (PC & ABS)
<b>weight (net)</b>	13.0 kg (28.7 lbs)
<b>power consumption</b>	16 W
<b>usage</b>	rocker switch (I/O) at the arm, 2-stages rocker switch (60/100 %)
<b>balance of articulation joints</b>	spring (weight compensation)
<b>class of protection</b>	I
<b>accessory</b>	sterilizable handle, adapter for suspended ceiling
<b>norms</b>	EN 60601-1, EN 60601-2-41, ETL/cETL
<b>special features</b>	sterilisable grip, maintenance free
<b>fastening</b>	ceiling mount
<b>system of protection</b>	IP 20
<b>order number</b>	D15617000 - pure white

### light distribution

