

# Suspended luminaire

VIVAA C 600 D15636000

# Waldmann **W**

ENGINEER OF LIGHT.



**Derungs**   
LIGHT FOR PEOPLE

<b>fitted with</b>	6 x LED module
<b>light distribution</b>	40% direct / 60% indirect
<b>Color Rendering (CRI)</b>	> 80
<b>color temperature</b>	4000K
<b>work equipment</b>	electronic converter, 0-10V
<b>connected load</b>	120-277V; 50/60Hz
<b>mains lead</b>	direct power supply
<b>luminaire body</b>	stainless steel
<b>weight (net)</b>	8.1 kg (17.9 lbs)
<b>power consumption</b>	70 W
<b>luminous flux</b>	7000 lumens
<b>lamp cover</b>	CDP micro prism (PMMA)
<b>class of protection</b>	I
<b>accessory</b>	light diffusing foil
<b>norms</b>	EN 60598-1, EN 60598-2-25, ETL/cETL
<b>room height</b>	ceiling drop 50 cm (1.6 ft)
<b>special features</b>	Suitable for screen work according to EN 12464-1, CDP micro prismatic screen, Suitable for emergency lighting units according to EN 50172
<b>fastening</b>	ceiling fastening (pendant)
<b>system of protection</b>	IP 20
<b>order number</b>	D15636000 - Stainless steel/pure white

## light distribution

