

# Examination Luminaire HALUX N30-1 P SV

# D15990000

# Waldmann **W**

ENGINEER OF LIGHT.



**Derungs**   
LIGHT FOR PEOPLE

**fitted with**  
**illuminance field @ 50cm**  
**illuminance @ 50cm**  
**color rendering index (CRI)**  
**color temperature**  
**work equipment**  
**mains lead**  
**luminaire body**

**weight (net)**  
**power consumption**  
**usage**  
**balance of articulation joints**  
**class of protection**  
**accessory**

**norms**  
**special features**  
**fastening**  
**order number**

LED module - energy efficiency category A+  
Ø 18cm  
30,000lx  
> 93  
4400K  
electronic plug-in transformer  
approx. 5.6ft (1.7m)  
polycarbonate & acrylonitrile butadiene  
styrene copolymer (PC & ABS)  
approx. 2.9lbs (1.3kg)  
8W  
keypad at luminaire head  
friction  
II  
roll support, rail fastening with removal  
protection, table clamp with removal  
protection, universal fastening with removal  
protection, extension arm with removal  
protection, wall bracket with removal  
protection  
EN 60601-1; EN 60601-2-41  
continuously dimmable, maintenance free  
fastening pin (Ø 16mm)  
D15990000 - pure white

## light distribution

