

RL(\$ Series

Waldmann W

ENGINEER OF LIGHT.



Applications: The RL40 Series is a waterproof, linear fluorescent tubular luminaire that features a slim 1.57" (40mm) outer diameter tube. This specially designed polymer tube is impact and UV radiation resistant for long term tube life and color clarity. The smaller design is architecturally pleasing and ideal for illuminating compact areas where space is limited. A variety of mounting brackets are available for installation in both exterior and interior applications with simple installation and low maintenance for an energy efficient lighting solutions.










Part#		Type
Project		
Comments		Date
Prepared by		

Sample Number: RL40 - E - 32 - B - 120 - S - 41 - 10FT - SS - D - N

RL40-


Ballast Type	Lamping	Dimming (Remote Ballast Only)	Voltage	Tube Color	Color Temp	Options			
						Cord (ft.) or (N)one	Mounting	Decorative End Caps	Canopy
Internal Remote									

Mounting Options:

		Pendant Ring Bracket Ring: Anodized Aluminum Wire: Stainless Steel Part # 190173029-00071022
		Surface Ring Bracket Ring: Anodized Aluminum Screw: Stainless Steel Part # 190177019-00092092
		Pendant Strap Bracket Strap: Stainless Steel Wire: Stainless Steel Part # 190179049-00071053
		Surface Strap Bracket Strap: Stainless Steel Surface Mount: Stainless Steel Part # 190174019-00092088
		Surface Spring Clip Spring Band: Galvanized Steel Part # 306266022-00085912

TECHNICAL SPECS:

- Voltage:** 120-277V, 50/60Hz
- Lamp Technology:** 1 x Fluorescent T5, T5HO, or T8
- Ballast:** Standard Electronic or Remote Dimming
- Waterproof:** IP67 Protection
- Tube:** PMMA Polymer Acrylic; Clear or Satine
- Light Distribution:** 180°
- Cable Gland:** Side entry located at end cap, sealed with "O" ring
- Cord:** Optional, not included
- Mounting:** Surface, Horizontal or Vertical pendant available
- Dimensions:** Ø1.57 in. [40 mm]; length varies by lamp type
- Safety:** ETL/cETL
- Dimming available with remote ballast only**




Shown for 32W T8. Complete IES files available at www.waldmannlighting.com

Dimensional Layout

a = Length

b = Light Opening



Waldmann Lighting Company
9 West Century Drive
Wheeling, IL 60090

www.waldmannlighting.com
Tel (800) 634-0007
Fax (847) 520-1730

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials. Technical specification sheets that appear on www.waldmannlighting.com are the most recent versions and supersede all other versions that exist in any other printed or electronic form. 6-2013