



fitted with

work equipment
 connected load
 power consumption
 power factor
 lens
 luminous flux
 luminous efficacy
 Narrow Beam Angle
 distribution
 light color
 color rendering index (CRI)
 consistent white light of unified glare
 Anti-glare Honeycomb, UGR
 system of protection
 class of protection
 technology
 luminaire body
 lamp cover
 weight (net)
 fastening
 minimum ambient temperature
 maximum ambient temperature
 impact strength
 life L70B10 / L70B50
 installation height
 dimensions

LED

dimmable electronic driver; 1-10V
 120-277V; 50/60Hz approx.
 100 W
 approx. 0,950
 narrow beam
 approx. 13000 lm
 approx. 130 lm/W
 60°
 100% direct
 neutral white, approx. 5000 K
 > 80
 < 3 SDCM
 < 23
 IP 65
 I
 continuously dimmable
 aluminium, powder-coated,
 acrylic clear
 approx. 5.6 kg (12.4 lbs)
 optional mounting brackets available
 -30 °C (-22 F)
 +50 °C (122 F)
 IK08
 Ta 25°C: 69,000h / 78000h
 3-20m (9.84 ft - 65.6 ft)
 a; 360mm (14.17in), b; 210mm (8.26in)



Beam Angle

