



fitted with

work equipment  
 connected load  
 power consumption  
 power factor  
 lens  
 luminous flux  
 luminous efficacy  
 Narrow Beam Angle  
 distribution  
 light color  
 color rendering index (CRI)  
 consistent white light of unified glare  
 Anti-glare Honeycomb, UGR  
 system of protection  
 class of protection  
 technology  
 luminaire body  
 lamp cover  
 weight (net)  
 fastening  
 minimum ambient temperature  
 maximum ambient temperature  
 impact strength  
 life L70B10 / L70B50  
 installation height  
 dimensions

LED

dimmable electronic driver; 1-10V  
 120-277V; 50/60Hz approx.  
 200 W  
 approx. 0,950  
 narrow beam  
 approx. 26000 lm  
 approx. 130 lm/W  
 60°  
 95% direct / 5% indirect  
 neutral white, approx. 5000 K  
 > 80  
 < 3 SDCM  
 < 23  
 IP 65  
 I  
 continuously dimmable  
 aluminium, powder-coated,  
 acrylic clear  
 approx. 5.6 kg (12.4 lbs)  
 optional mounting brackets available  
 -30 °C (-22 F)  
 +50 °C (122 F)  
 IK08  
 Ta 25°C: 69,000h / 78000h  
 3-20m (9.84 ft - 65.6 ft)  
 a; 360mm (14.17in), b; 210mm (8.26in)



Distribution



Beam Angle

