



fitted with

- work equipment
- connected load
- power consumption
- power factor
- lens
- luminous flux
- luminous efficacy
- Wide Beam Angle
- distribution
- light color
- color rendering index (CRI)
- consistent white light of unified glare
- Anti-glare Honeycomb, UGR
- system of protection
- class of protection
- technology
- luminaire body
- lamp cover
- weight (net)
- fastening
- minimum ambient temperature
- maximum ambient temperature
- impact strength
- life L70B10 / L70B50
- installation height
- dimensions

LED

- dimmable electronic driver; 1-10V
- 120-277V; 50/60Hz approx.
- 150 W
- approx. 0,950
- wide beam
- approx. 19500 lm
- approx. 130 lm/W
- 80°
- 95% direct / 5% indirect
- neutral white, approx. 5000 K
- > 80
- < 3 SDCM
- < 23
- IP 65
- I
- continuously dimmable
- aluminium, powder-coated,
- acrylic clear
- approx. 5.6 kg (12.4 lbs)
- optional mounting brackets available
- 30 °C (-22 F)
- +50 °C (122 F)
- IK08
- Ta 25°C: 69,000h / 78000h
- 3-20m (9.84 ft - 65.6 ft)
- a; 360mm (14.17in), b; 210mm (8.26in)



Distribution



Beam Angle

